

N-STAR c

S-band Commercial Communications Satellite

FACT SHEET



Mission Description

Built for NTT DoCoMo, N-STAR c is furthering NTT's vision of providing wireless service for a multitude of applications including mobile telephony, data transfer and maritime communications. N-STAR c provides an improved signal to users, allowing better voice quality and smaller mobile phones for the Japanese users.

N-STAR c operates in the S-band with a C-band feeder link. The satellite is located at 136 degrees East Longitude and was launched in early July 2002 on an Ariane 5 rocket. N-STAR c is optimized for a ten-year minimum life on-orbit, and is augmenting service provided by the company's existing satellites.

Lockheed Martin supplied the payload, which was integrated onto the Orbital ATK GEOStar[™]-2 bus in Orbital ATK's Dulles, Virginia facility. Final integration and test was performed at the Lockheed Martin Commercial Space Systems facilities in Newtown, Pennsylvania. In addition to the satellite bus, Orbital ATK provided the ground system and procured the launch vehicle.

Spacecraft

N-STAR c is based on Orbital ATK's highly successful Geosynchronous Earth Orbit (GEO) communications satellites which are able to accommodate all types of commercial communications payloads and are compatible with all major commercial launchers. The company's GEOStar product line includes the GEOStar-2 design, which is optimized for smaller satellite missions that can support up to 5.0 kilowatts of payload power. Orbital ATK has also developed the higher-power GEOStar-3 spacecraft design, delivering the next increment of payload power for applications between 5.0 and 8.0 kilowatts, allowing Orbital ATK to offer its innovative and reliable satellite design to the medium-class of communications satellites.

FACTS AT A GLANCE

Coverage:

Japan



Mission:

S-band mobile communications

Customer:

NTT Mobile Communications Network

N-STAR c

Specifications

Spacecraft

Launch Mass: 1,625 kg (3,582 lb.)

Redundancy: Typically 2-for-1, minimum

Solar Arrays: Multi-junction Gallium Arsenide cells Stabilization: Zero momentum; 3-axis stabilized

Pointing: <0.12° circular error

Payload Power: ~1.4 kW

Propulsion: Liquid bi-propellant transfer orbit system;

monopropellant (hydrazine) on-orbit

Mission Life: 10 year minimum, tank capacity for >12

years

Orbit: 136° East Longitude

Payload

Frequency: S-band mobile communications, C-band

feeder link

Repeater: S-band: 288 W multiport amplifier (three

5-for-4 groups of 24 W solid-state power

amplifiers)

C-band: 2-for-1 solid state power amplifiers

(13 W)

Antenna: 5.1 m unfurlable


Launch

Launch Vehicle: Ariane 5

Site: Kourou, French Guiana

Date: July 5, 2002

N-STAR c Mission Profile



Mission Partners

NTT DoCoMo

NTT DoCoMo is Japan's premier mobile communications company, which provides wireless voice and data communications to tens of millions of subscribers. NTT DoCoMo is the creator of W-CDMA air interface technology, as well as the groundbreaking mobile i-mode service.

Orbital ATK

Orbital ATK provided the system design and was responsible for the assembly, integration and test of the spacecraft bus. Orbital ATK also provided the ground station and procured the launch services.

Lockheed Martin Commercial Space Systems

Lockheed Martin, as the prime contractor, participated in integration and test, and provided the communications payload.

Arianespace

Launch provider



N-STAR c mated to Ariane 5 prior to its July 5, 2002 launch



N-STAR c was launched aboard an Ariane 5 rocket.